

DSC-600



DS CARRIER 600

DSC-600



DSC-600

Explore better solutions
brought to you by DESCO



DS CARRIERS

TECHNICAL SPECIFICATIONS

		DS Carrier 600	DS Carrier 800
DIMENSIONS			
Length	M	6.4 / 7.6	7.6 / 9.4
Width	M	2.1	2.2
Height	M	2.5	2.7
Weight	Ton	6.0 / 6.5	7.5 / 8.5
Length of Deck	M	5.0 / 6.2	6.2 / 8.0
ENGINE			
		Hyundai / Doosan Engine	
Power	hp	74 / 100	100
Fuel capacity	L	120	150
HYDRAULIC SYSTEM			
		Single or Double pump	
Model		K3V63S / K3V63DP / K3V112S	
Flow Rate	LPM	95 / 190 / 170	
Operating Pressure	Bar	280	
Hyd. Oil Tank	L	120	150
TRAMMING			
		Solar 55	Solar 75
Tramming Speed	km/h	2.5 ~ 4.0	
Gradeability		25°	
Loading Capacity	Ton	6.0	12.0
Track Shoes Width	mm	400	450
Track Shoes		Steel / Rubber	Steel
ELECTRICAL SYSTEM			
		24V / 12V	
CONTROL PANEL			
		All levers & gauges are grouped at the operator's station	
HYD. JACKS & RIGGERS			
		Four jacks & riggers / Self-loading system	
OPTIONAL LIST			
Remote Control for Tramming		Hetronics	
Mud Pump		300LPM, 500LPM, 800LPM	
Auxiliary Fuel Tank		Tank (1000L), Fuel Pumping Gun & Hose Reel System (20M)	
Auxiliary Power Pack		45LPM ~ 100LPM @ 180 ~ 210BAR	
Crawler		Steel with rubber pad	